

Technical proposal for JX-DC-575M3800M-4310Fx Coupler

- ◆ IP65
- ◆ High Performance
- ◆ High Reliability

Revision History

Version	Date	Author	Revision description	Comment
V1.0	2019/04/24	Lin liqun	Created	/
V1.1	2020/09/02	Lin liqun	Update Mechanical specifications and front panel layout and Electrical specifications	

JING XIN MICROWAVE TECHNOLOGY CO.,LTD

E-mail: sales@cdjx-mw.com Web: <http://www.cdjx-mw.com>

TEL: +86-28-85026087 FAX: +86-28-65026087 ext.8033 Zip Code:610045

Add: No.65,West 1st Wu Ke Road, Wu Hou District, Cheng Du City, Si Chuan Province, China.

Table of content

Technical proposal for JX-DC-575M3800M-4310Fx Coupler	1
1. Mechanical layout.....	2
2. Electrical specifications	3

Figures

Figure 1 JX-DC-575M3800M-4310Fx front panel layout.....	3
---	---

Tables

Table 1 Mechanical specifications	2
Table 2 Electrical specifications.....	3

1. Mechanical layout

Table 1 Mechanical specifications

Dimension	LxWxH: 136mm x 50mm x 26mm
Connectors	4.3-10/Female
Finish	Black / Gray / Gold / Frosted Matte Black
Ingress protection	Indoor/Outdoor Use, IP65
Notes	Material shall be RoHS 6/6

JING XIN MICROWAVE TECHNOLOGY CO.,LTD

E-mail: sales@cdjx-mw.com Web: <http://www.cdjx-mw.com>

TEL: +86-28-85026087 FAX: +86-28-65026087 ext.8033 Zip Code:610045

Add: No.65,West 1st Wu Ke Road, Wu Hou District, Cheng Du City, Si Chuan Province, China.




Figure 1 JX-DC-575M3800M-4310Fx front panel layout

2. Electrical specifications

Table 2 Electrical specifications

Item	Parameter	Specification							
1	Frequency range	575-3800MHz							
2	Model number	JX-DC-5 75M380 0M-431 0F5	JX-DC-5 75M380 0M-431 0F6	JX-DC-5 75M380 0M-431 0F7	JX-DC-5 75M380 0M-431 0F10	JX-DC-5 75M380 0M-431 0F13	JX-DC-5 75M380 0M-431 0F15	JX-DC-5 75M380 0M-431 0F20	JX-DC-5 75M380 0M-431 0F30
3	Coupling	5±1.0 dB	6±1.0 dB	7±1.0 dB	10±1.0 dB	13±1.0 dB	15±1.0 dB	20±1.0 dB	30±1.2d B
4	Insertion loss	2.3dB	1.8dB	1.3B	0.8dB	0.5dB	0.5dB	0.4dB	0.3dB
5	VSWR	≤1.25:1							
6	Directivity	20dB@575-3600MHz							
		18dB@3600-3800MHz							
7	PIM3	-155dBc@2x43dBm (Measured reflection 900 MHz, 1800 MHz)							
8	Power rating	300W							
9	Impedance	50Ω							
10	Temperature range	-35 to +85°C							

JING XIN MICROWAVE TECHNOLOGY CO.,LTD

E-mail: sales@cdjx-mw.com Web: <http://www.cdjx-mw.com>

TEL: +86-28-85026087 FAX: +86-28-65026087 ext.8033 Zip Code:610045

Add: No.65, West 1st Wu Ke Road, Wu Hou District, Cheng Du City, Si Chuan Province, China.