

# Technical proposal for JX-CC5-832M2570M-45S1 Cavity Combiner

- ◆ Low Insertion Loss
- ◆ High Rejection
- ◆ Small volume
- ◆ High Reliability

## Revision History

Version	Date	Author	Revision description	Comment
V1.0	2020/04/30	Sam Chen	Created	/

**JING XIN MICROWAVE TECHNOLOGY CO.,LTD**

E-mail: [sales@cdjx-mw.com](mailto:sales@cdjx-mw.com) Web: <http://www.cdjx-mw.com>

TEL: +86-28-85026087 FAX: +86-28-65026087 ext.8033 Zip Code:610045

Add: No.65,West 1st Wu Ke Road, Wu Hou District, Cheng Du City, Si Chuan Province, China.

## Table of content

Technical proposal for JX-CC5-832M2570M-45S1 Cavity Combiner.....	1
1. Mechanical layout.....	3
2. Electrical analysis.....	4
2.1 Schematic diagram of the Combiner.....	4
2.2 Electrical specifications .....	4

## Figures

Figure 1 JX-CC5-832M2570M-45S1 front panel layout .....	3
Figure 2 Topology of the Combiner .....	4

## Tables

Table 1 Mechanical Specifications @ JX-CC5-832M2570M-45S1 .....	3
Table 2 Electrical specifications @ JX-CC5-832M2570M-45S1 .....	4

**JING XIN MICROWAVE TECHNOLOGY CO.,LTD**

E-mail: [sales@cdjx-mw.com](mailto:sales@cdjx-mw.com) Web: <http://www.cdjx-mw.com>

TEL: +86-28-85026087 FAX: +86-28-65026087 ext.8033 Zip Code:610045

Add: No.65,West 1st Wu Ke Road, Wu Hou District, Cheng Du City, Si Chuan Province, China.

## 1. Mechanical layout

Table 1 Mechanical Specifications @ JX-CC5-832M2570M-45S1

Dimension	LxWxH: 110mm x 110mm x 65mm (70.0mm Max)
Port connectors	SMA-Female
Weight	< 1.0 kg
Finish	Sliver
Notes	Material shall be RoHS 6/6




Figure 1 JX-CC5-832M2570M-45S1 front panel layout

**JING XIN MICROWAVE TECHNOLOGY CO.,LTD**

E-mail: [sales@cdjx-mw.com](mailto:sales@cdjx-mw.com) Web: <http://www.cdjx-mw.com>

TEL: +86-28-85026087 FAX: +86-28-65026087 ext.8033 Zip Code:610045

Add: No.65,West 1st Wu Ke Road, Wu Hou District, Cheng Du City, Si Chuan Province, China.

## 2. Electrical analysis

### 2.1 Schematic diagram of the Combiner




Figure 2 Toplogy of the Combiner

### 2.2 Electrical specifications

Table 2 Electrical specifications @ JX-CC5-832M2570M-45S1

Item	Parameter	IN-OUT
1	Frequency range	832-862 MHz&880-915 MHz&1710-1785MHz&1920-1980 MHz&2500-2570 MHz
2	Return loss	≥18 dB
3	Insertion loss	≤1.0 dB
4	Rejection at all stop bands	≥45dB@791-821MHz&925-960MHz&1805-1880MHz&2110-2170MHz&2620-2690MHz
5	power	+20dBm CW Max
7	Impedance	50 Ω

**JING XIN MICROWAVE TECHNOLOGY CO.,LTD**

E-mail: [sales@cdjx-mw.com](mailto:sales@cdjx-mw.com) Web: <http://www.cdjx-mw.com>

TEL: +86-28-85026087 FAX: +86-28-65026087 ext.8033 Zip Code:610045

Add: No.65,West 1st Wu Ke Road, Wu Hou District, Cheng Du City, Si Chuan Province, China.